

# **KF40 WIDE ANGLE**ASPIRATED FOAM WATER NOZZLE

**NDD405** 

- Under Equipment Foam Application Device
- Superior Foam Quality
- Stainless Steel Construction
- Seawater
- AR-AFFF/AFFF and Protein Compatible



## Description


The KF40 wide angle directional foam/water nozzle is constructed of stainless steel, and operates at a 3.1 K-factor. The nozzle is capable of being mounted in any position between full upright to full pendant. The nozzle is suitable for use with AR-AFFF/AFFF and Protein foam solutions.

#### **Features**

- Capable of being mounted in any position between full upright to full pendant
- Lightweight, investment cast welded, high-grade stainess steel construction
- BSP or NPT inlet
- Special order inlets available upon request

## **Applications**

Ideal for containment areas, under hazard, under/over hazard, loading racks, heliports, and process areas.



**Note:** Spray pattern based on nozzle mounted 36" (914.4 mm) above grade.

#### **Technical Data**

#### **Description:**

Foam/Water Nozzle

#### Manufacturer:

National Foam

## Model:

Wide Angle

# K-factor:

3.1

# Connection:

34" FNPT (w/o adapter 34" BSP)

# **Operating Range:**

Minimum:. 30 psi (2.07 bar) Maximum: 100 psi (6.89 bar)


## **Materials of Construction:**

Body: 316 SS Deflector: 316 SS Finish: Plain

| Flow / Pressure Chart       |                            |  |
|-----------------------------|----------------------------|--|
| Inlet Pressure<br>psi (bar) | Foam Solution<br>gpm (lpm) |  |
| 100 (6.89)                  | 31 (117)                   |  |
| 80 (5.52)                   | 28.7 (109)                 |  |
| 70 (4.83)                   | 26 (98)                    |  |
| 50 (3.45)                   | 22 (83)                    |  |
| 30 (2.07)                   | 16.5 (62)                  |  |

| Spray Pattern "In Air" Range Data |                        |                       |
|-----------------------------------|------------------------|-----------------------|
| Inlet Pressure<br>psi (bar)       | "L" - Length<br>ft (m) | "W" - Width<br>ft (m) |
| 100 (6.89)                        | 5.7 (1.74)             | 10 (3.05)             |
| 50 (3.45)                         | 4.7 (1.43)             | 5.7 (1.74)            |
| 30 (2.07)                         | 4 (1.22)               | 2 (0.61)              |

Note: Range is increased as foam 'pushes' across spill during operation.



| ORDERING INFORMATION |                                    |
|----------------------|------------------------------------|
| Part Number          | Description                        |
| 1255-2834-2          | KF40 Nozzle, Wide Angle 3/4 (F)NPT |

06/19 NDD405 (Rev C)

National Foam

350 East Union Street, West Chester, PA 19382, USA 24hr **RED ALERT®**: 610-363-1400 • Fax: 610-431-7084

Page 1 of 1